POOL4-I



POOL4-I is the new generation of Commercial pool pumps integrating a new frequency inverter to get a great comfort and minimize the energy costs. The system allows the programming of several daily filtration cycles with different operating speed for each cycle. In installations with several POOL4-I the pumps automatically communicate and alternate to work the same amount of hours. Capable to work more than one pump at the same time.



Self ventiled wall support

Construction features							
Painting	cataphoresis						
Pump body, seal housing, diffuser	polypropylene + fiber glass						
Motor bracket	aluminum						
Impeller	Noryl®, marine bronze on request						
Mechanical seal	ceramic-graphite-AISI 316						
Motor shaft	stainless steel AISI 316						
Liquid temperature	max 40 °C						
Pre-filter cover	polycarbonate						
Support base	Noryl®						

Motor								
2 Poles induction motor	3~ 230V/400V-50Hz							
Insulation class	F							
Protection degree	IP55							
Integral system for pool control	with variable speed drive included							














POOL4-I



TYPE	P2			H (m)								Minimum
3~			rpm	6	8	10	12	14	16	DNA	DNM	size of suction
٥~	HP	kW		Q (m³/h)								pipe
POOL4-I 4-250	2,5	1,8	1450	53	43	32	18			110		110
POOL4-I 4-300	3	2,2	1450	62	54	43	26	10				125
POOL4-I 4-400	4	3	1450	74	66	56	42	29	14			140
POOL4-I 4-550	5,5	4	1450	123	104	84	57	30				160